



The AvediaPlayer m9325 Wi-Fi combines the delivery of HD video across a wide range of resolutions up to 1080p60, with an additional Ethernet port and large content storage capacity. An integrated Wi-Fi module enables organisations to deliver IPTV and digital signage content to the m9325 Wi-Fi wirelessly.



### Video Output

- HDMI v1.4b (with HDCP): 1080p, 1080i, 720p (50Hz/59.94Hz/ 60Hz), 576p, 576i (50Hz), 480p, 480i (59.94Hz/60Hz)

### Video Decoding

- MPEG-4 part 10 H.264 (ISO/IEC 14496/10)
- MPEG-2 (ISO/IEC 13818-2)
- Resolutions:
  - 1080i and 1080p @ 50Hz, 59.94Hz or 60Hz
  - 576i, 576p, 720p
  - 480i, 480p
  - 240p, 360p

### Audio Output

- HDMI: 2 or 6 Channel PCM or Bitstream

### Audio Decoding

- MPEG-1 Layer II (ISO/IEC 11172-3)
- AC3/EAC3
- AAC/HE-AAC
- Down-mixes multi-channel audio to stereo

### USB 2.0 Port

- Can be used for external storage & Human Interface Devices
- USB hot plug enables auto-mounting of USB devices

### Digital Signage

- ArtioSign® Display software (licensable option)

### Streaming

- MPEG2 Transport Stream (ISO/IEC 13818-1)
- UDP, HLS, RTP (6Mbps limit for HLS)
- IP multicast ; IP unicast
- IGMPv2/v3
- Video On-Demand: HLS, RTSP, HTTP

### Content Protection Support

- Decrypts HDCPv2.2 protected content
- Decrypts Samsung LYNK™ DRM protected content (live streams) from an AvediaStream g4415-1k Gateway. Samsung LYNK DRM Client licence required.
- Decrypts ARRIS SECUREMEDIA® DRM protected content (live streams and VoD) from an AvediaStream g4415-sm Gateway. Encryptonite ONE™ Server and client licence required.

### Infra-red/Control Options

- Built-in IR receiver
- 3.5mm jack for IR extender or tethered remote control
- IR keyboard and third party IR & USB remote controls supported
- TV control via Serial RS232 or HDMI CEC
- HDMI CEC Remote Control Passthrough

### Channel Management

- Using the AvediaServer Smart Control app
  - Set channel
  - Set volume/mute
- On-device channel management
  - SAP/SDP announcements
  - Channel access control
  - XML channel lists, static & hidden channels
- Channel redundancy & failover to channel or web page

### System

- CPU: ST40-300 540MHz
- RAM: 512MB
- Flash:
  - 256MB (for firmware and config)
  - 32GB (for content storage)
- OS: STLinux 2.4

### Built-in User Interface

- Channel selection menu
- Volume control
- Audio Language control
- DVB Subtitles (ETSI EN 300 743)
- Closed Captions (CEA-608 captions embedded in CEA- 708 data)
- Teletext subtitles

### Integrated Web Browsers

- Ekioh TV Browser for integration with Exterity and third party middleware
  - HTML5
  - CSS 3 & Dom 3
  - Image formats: png, jpeg

### Network

- Linux dual IPv4/IPv6 stack
- DHCP/DHCPv6 or Static IP addressing
- IEEE 802.3u 10/100Mbps MDIX Ethernet
- IEEE 802.3at POE+ PD
- IEEE 802.1X network authentication
- Simple Certificate Enrollment Protocol (SCEP) for 802.1X
- Second Ethernet port with 802.3af PSE Power Over Ethernet (POE) (requires PoE+ in or use of power supply avply-ps48-xx)
  - Max output: 7W (Class II)

### Management

- Fully integrated with all Exterity management tools:
  - Admin level management using AvediaServer Director & Site Manager applications
  - Day-to-day management using AvediaServer Smart Control application
  - HTTP/HTTPS device web interface; recommended browser: Chrome®
- Simple Certificate Enrollment Protocol (SCEP) for HTTPS

- SNMP
- UPnP device discovery
- RESTful API
- Console access via SSH and Serial RS232 Admin Port
- Terminal Control Interface (TCI) for control system integration
- Event logging via Syslog (local and remote)
- Firmware upgrade via TFTP
- Configuration backup/restore via TFTP
- Secure Mode option to lock down media player access

**Additional Features**

- Accelerated channel change mode (sub 500ms (transcoder required))
- Video wall capability
- Unit-to-unit sync capability
- Low end-to-end latency (sub 400ms end-to-end latency (specific settings required. Contact Exterity Support for more information))

**Wi-Fi**

- Integrated Wi-Fi module enables client operation to join wireless networks
- 802.11ac/n/g/b/a
- Channels 1 - 14 (2.412 - 2.484 GHz)
- Security: WEP, WPA, WPA2, AES, TKIP, CKIP

**Optional Accessories**

- TV and under- desk mounting brackets
- IR and wired remote controls and extenders
- Power supplies for non-POE environments
- ArtioSign® Display digital signage licence

**Protocols**

IP (RFC791), UDP (RFC768), TCP (RFC793), ARP (RFC826), DNS (RFC1035), DHCP (RFC2131), ICMP (RFC0792), IGMP v3 (RFC 3376), TFTP (RFC1350), HTTP (RFC2616), Syslog (RFC3164), NTP (RFC1305), SAP (RFC2974),SDP (RFC4566), RTP (RFC3550), RTSP (RFC2362), SNMPv1/ v2c (RFC1157/ RFC1901), HLS, HTTPS (RFC2818), 802.1X (RFC3580), SSDP, IPv6 (RFC 8200), DHCPv6 (RFC 8415), SLAAC (RFC 4862), MLD (v2) (RFC 3810), NDP (RFC 4861)

**Environment**

- Operating temperature: 0 ...+40°C / +32 ... +122°F
- Storage temperature: -20 ...+70°C / -4 ... +158°F
- Operating Relative Humidity: 5 – 95% (non-condensing)

**Regulatory**

CE:

- IEC 62368-1: 2014
- EN 62368-1:2014+A11:2017
- EN55032:2012 + corrigenda Aug 2012 & Dec 2012
- EN55024:2010 + A1:2015
- EN 61000-3-2:2014
- EN 61000-3-3:2013

UL/CSA:

- UL62368-1:2014
- CSA C22.2 No. 62368-1, Rev. December 01, 2014

FCC:

- 47CFR:2011 Part 15, Sub Part B
- ANSI C63-4:2014

ACMA:

- AS/NZS 62368.1.2014 ( ed.2)

**Wi-Fi Module Regulatory**

USA

- FCC Part 15, Subpart C 15.247 (WLAN)
- FCC Part 15, Subpart C 15.247 (BT)
- FCC Part 15, Supbart E 15.407 (DFS)

Canada

- ICES-003:2012 Issue 5, Class B
- RSS-Gen, Issue 4, November 2014
- RSS-102, Issue 5, March 2015
- RSS-247, Issue 1, May 2015

Mexico

- NOM-121-SCT1-2009

EU

- EN300 328 V1.9.1
- EN301 489-1 V1.9.2
- EN301 489-17 V2.2.1
- EN301 893 V1.8.1
- EN62311:2008
- EN55022:2011

Australia, New Zealand

- AS/NZS 4268: A1: 2013
- AS/NZS 2772.2

Japan

- ARIB STD-T66 (v3.7), MIC notice 88 Appendix 43 RCR STD-33 (v5.4), MIC notice 88 Appendix 44
- ARIB STD-T71 (v6.1), MIC notice 88 Appendix 45

Country Transmitter IDs

- USA FCC ID R68PW2050
- Canada IC ID 3867A-PW2050
- Mexico RCPLAPW15-2109
- Japan ID 201-152843
- China SRRC 2015AJ6847 (M)

**Dimensions**

- 35mm (H) x 230mm (L) x 140mm (D)
- Weight 0.6kg

**Power**

- Typical: 9W, Maximum: 13.5W
- DC Jack 48V
- PoE 802.3af PD

**MTBF**

- Calculated to MIL-HDBK-217F, notice 2: 77202 hours (8.8 years)

**In the Box**

- AvediaPlayer m9325 Wi-Fi Media Player, single HD AV (HDMI) out, 32 GB storage, Wi-Fi, 2-port Ethernet switch, PoE (802.3af), includes ArtioGuest client licence
- Product Safety Brochure (hard copy)



UK Headquarters  
+44 (0) 1383 828 250  
Singapore  
+65 3157 9352

Australia  
+61 (0) 2905 61199  
South Africa  
+27 (0) 11 469 0465

Europe  
+33 (0) 3 52 84 01 23  
United Arab Emirates  
+971 (4) 447 0604

Saudi Arabia  
+966 (11) 834 3530

United States of America  
+1 201 580 2130

e: info@exterity.com

w: www.exterity.com



© 2021 Exterity Ltd. All rights reserved. The Exterity logo, ArtioGuest, ArtioPortal, ArtioSign, AvediaPlayer, AvediaServer and AvediaStream are trademarks or registered trademarks of Exterity Ltd. The information and specification are subject to change without prior notice. Exterity tries to ensure that all information in this document is correct but does not accept liability for any error or omission.