



Exterity provides hardware platforms and software applications that enable you to capture TV and video content directly from any source and manage its delivery, as channels or within digital signage, to any connected device on your existing network, as well as beyond the corporate LAN via WAN, Wi-Fi and the Internet to any device, in any location.

There are three groups of Exterity products:

### AvediaStream

This group includes:

- IPTV head end products that stream video content onto an IP network.
- Media Players that decode streams from IP networks for use on displays or computer desktops.

### AvediaServer



IPTV Server platform for applications that deliver advanced functionality.

### ArtioGuest, ArtioSign, ArtioPortal

Deliver live TV and VoD combined with program information and specialist services to unlimited numbers of users.

The accessories described here apply to one or more of these product groups and add to the standard features or allow interconnection between an Exterity product and specific external devices.



## 1. General Accessories

Accessory	Description	Order Code	Applies to	
RJ-45 to 9-pin D-type serial adapter	Adapter that allows an RJ45 cable used for serial control of an Exterity device to be connected to a standard serial plug.	access-srl	AvediaStream Media Players AvediaStream Gateways	
USB to RJ-45 serial cable	Cable to allow serial control of Exterity device from a USB connection.	access-usb	AvediaStream Encoders AvediaStream t36xx Transcoder	





## 2. AvediaStream

For AvediaStream Media Player brackets please see the “AvediaStream Installation Accessories” datasheet.

### 2.1 AvediaStream Media Player Power Supplies

Accessory	Description	Order Code	Applies to	
External power supply and mains cord (Product shown here is UK version)	Power supply for use where Power Over Ethernet is not available 110-240v (50Hz-60Hz) 12W	avply-psu -uk (BS 1363/A) -us (NEMA 1-15P) -eu (CEE 7XVI) -au (AS/NZS 3112) -sa (SABS 164-1)	AvediaStream 93- and 94-series Media Players (except m9325)	
External power supply and mains cord (Product shown here is UK version)	Power supply for use where Power Over Ethernet is not available 110-240v (50Hz-60Hz) 25W	avply-ps48-## -uk (BS 1363/A) -us (NEMA 1-15P) -eu (CEE 7XVI) -au (AS/NZS 3112) -sa (SABS 164-1)	AvediaStream m9325/m9325-Wi-Fi Media Players	

### 2.2 AvediaStream Media Player IR Remotes and Extenders

Accessory	Description	Order Code	Applies to	
IR Remote Control	Remote control for media players and certain Hospitality SmartTVs. Includes 2 pre-installed batteries (ER03X/UM4/AAA - Not restricted under special provision (SP) A123)	avply-irrc	AvediaStream 93-, 94- and 96-series Media Players  Certain Hospitality SmartTVs	
IR Remote Control & IR extender	Remote control plus 1.5 meter IR extender cable enabling media player to be mounted out of sight. Supplied with batteries pre-installed	avply-irrcck	AvediaStream 93-, 94- and 96-series Media Players	
Tethered Remote Control	Non-IR remote control connected to media player by 1.8 meter cable	avply-rct	AvediaStream 93-, 94- and 96-series Media Players	
Standard 38KHz IR extender	1.5m IR extender cable operating at 38KHz to work with the standard IR remote control and enabling media player to be mounted out of sight	avply-ir38	AvediaStream 93-, 94- and 96-series Media Players	

### 2.3 AvediaStream Media Player IR and Serial Cables

The following IR and serial cables can be used with AvediaStream 93- and 94-series Media Players.

Accessory	Description	Order Code
LG* 3.5mm IR port to media player IR port	Enables control of Exterity Media Players using Exterity IR remote commands passed through an LG TV	avply-ir-lg1
LG* DB9 to media player IR and serial ports	Enables control of Exterity Media Players using Exterity IR remote commands passed through an LG TV. Also enables serial control of LG TVs from Exterity Media Players.	avply-irser-lg2
Philips* RJ-48 serial port to media player serial port	Enables serial control of Philips TVs from Exterity Media Players	avply-ser-phi1
Samsung* 3.5mm IR port to media player IR port	Enables control of Exterity Media Players using Exterity IR remote commands passed through a Samsung TV	avply-ir-sam1
Samsung* RJ12 to media player IR and serial ports	Enables serial control of Samsung TVs from Exterity Media Players	avply-irser-sam2
Samsung* 3.5mm serial port to media player serial port	Enables serial control of Samsung TVs from Exterity Media Players	avply-ser-sam3
Samsung* RJ-12 serial port to media player serial port	Enables serial control of Samsung TVs from Exterity Media Players	avply-ser-sam4
Sony* RJ-12 serial port to media player serial port	Enables serial control of Sony TVs from Exterity Media Players	avply-ser-son1


\* Please contact Exterity Technical Support for tested TV model numbers

### 2.4 AvediaStream Chassis Accessories

Accessory	Description	Order Code	Applies to	
AvediaStream chassis module blanking plate	Extra blanking plate to cover an unused chassis blade slot	avstr-cbpl	AvediaStream c1210 and c1103 chassis	
AvediaStream c1210 fan module	Replacement cooling fan for c1210 24V DC 1.2W	c1210-fan	AvediaStream c1210 chassis	
AvediaStream c1210 chassis power supply and mains cord	Additional power supply to add redundancy or extra power capacity to c1210. Country code specifies mains cord. 110-240v (50Hz-60Hz) 300W 1.0kg	c1210-pwr -uk (BS 1363/A) -us (NEMA 5-15P) -eu (CEE 7/7) -au (AS/NZS 3112) -sa (SABS 164-1)	AvediaStream c1210 chassis	
AvediaStream c1210 monitor blade	Adds chassis and blade monitoring functions to ten blade chassis	c1210-mon	AvediaStream c1210 chassis	
Infra-red transmitter for SD and HD encoders	Active cable that allows the encoder to act as an infra-red remote control for controlling other devices. e.g. Satellite receivers, DVD players or media players	access-irt	SD and HD encoders	

### 3. AvediaServer

#### 3.1 Power Supplies

Accessory	Description	Order Code	Applies to	
Replacement AvediaServer c1565 power supply and mains cord	Power supply AC Input Rating 100-240V / 4-1.7A/50-60Hz DC Output 400W:+12V/33A Country code specifies mains cord	c1565-pwr -uk (BS 1363/A) -us (NEMA 5-15P) -eu (CEE 7/7) -au (AS/NZS 3112) -sa (SABS 164-1)	AvediaServer c1565	
Replacement AvediaServer c1585 power supply and mains cord	Power supply AC Input Rating 100-240V / 7.4-3.1A/50-60Hz DC Output 740W:+12V/61A Country code specifies mains cord	c1585-pwr -uk (BS 1363/A) -us (NEMA 5-15P) -eu (CEE 7/7) -au (AS/NZS 3112) -sa (SABS 164-1)	AvediaServer c1585	